

## Technical Data Sheet

### Description:

Color Restorer is a ready to use solvent based sealer containing superior synthetic resin. Color Restorer is wet activated, water and oil resistant. Color Restorer is recommended for rough, porous, and absorbent natural and cast stones.

### Characteristics & Properties:

Characteristics as follows:

- Brightens faded stone
- Wet-effected
- Water and dirt resistance
- Allows the stone to breathe
- Weather-resistance
- No unpleasant odor
- Patented : KP 10-1429888

Technical data:

- Appearance: liquid
- Color: clear to pale yellow
- Odor: characteristic
- Coverage: approx. 10~30m<sup>2</sup>/L
- Density: approx. 0.98 g/cm<sup>3</sup>
- Flash point: 34°C
- Reduction of water absorbency: approx. 90-95%

### Field of Use:

Marble, slabs, slate, lime stone, granite, solid surfaces, engineered stone and concrete.

### Method of Use:

1. The surface to be treated must be clean and absolutely dry.
2. Apply undiluted and even-treated with a paint-brush, roller, mop, or spray.
3. Apply 15~30m<sup>2</sup>/liter color restorer on the surface
4. Rub gently to favor the penetration and to remove eventual excess of product to avoid its drying on the surface.
5. According to temperature allow surface to dry 3~4 hours.

**Color Restorer**

6. Drying is completed 24 hours after the application.
7. Tools and excess treated surfaces can be cleaned with acetone.
8. For very absorbent substrates or for more color restorer effect, more wet effect, a second application is necessary after 10~15minutes of first application.

**Special hints**

1. Do not apply on humid substrates/materials. Apply on perfectly dry surfaces.
2. Remove the excess of product before it dries on the surface.
3. ConfiAd® Color Restorer must not be used on polished, glazed, damp surfaces, burnt surfaces such as cotto.
4. Objects which are sensitive to solvents around the working area must be protected.
5. Do not allow the sealer to dry without removing the excess. Dry residues will not be removable after 4~5hours.

**Storage:**

Storage temperature: Between 5°Cand 30°C

Must be applied to material at temperature between 5°Cand 30°C

Shelf life: 1 year approx. in original packing, if stored in a cool place free from frost.

**Environmental Protection:**

Contains solvents, free of chlorinated hydrocarbons.

Do not flush down drain.

Disposal: liquid product is classified as special waste.

Containers are made of environmentally friendly tin plate.

Clean containers can be recycled through collection systems.

**Safety:**

First Aid Procedures: Remove contaminated soaked clothing immediately. In case of inhalation, move victim to open area. In the event of symptoms refer for medical treatment. In case of contact with skin wash off immediately with soap and water. In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion, do not induce vomiting. If swallowed by mistake drink plenty of water and seek medical treatment.

Emergency Procedures: In case of spill or other release, take up with absorbent material (e.g. sand, sawdust, general-purpose binder). In case of fire formation of dangerous gases possible. Suitable extinguishing material: foam, dry powder, carbon dioxide, sand.

Additional information is listed on the Material Safety Data Sheet.

**Packing:**

24 tins of 250ml, 12 tins of 1L

The composition of the tins is Steel (ACC). After use, comply with the local and national regulations currently in force regarding recycling.

Our packing is conformed as per U.N. rules for inland transport (A.D.R.) and by sea (I.M.O.) for transportation via air refer to updated rules (I.A.T.A.). For further information regarding transport please check MSDS.

**Note:**