

Dimensions & Inspections

1. Dimensions

| Length (in/mm) | Width (in/mm) | Thickness (in/mm) | Weight (lb/kg) |
|----------------|---------------|-------------------|-----------------|
| 118" / 3,000mm | 55" / 1,400mm | 0.75" / 20mm | 450 lbs / 204kg |
| | | 1.125" / 30mm | 675 lbs / 306kg |
| 126" / 3,200mm | 63" / 1,600mm | 0.75" / 20mm | 548 lbs / 248kg |
| | | 1.125" / 30mm | 820 lbs / 372kg |

2. Inspections

| Contents | Required Details |
|-------------------|--|
| Length, Width | Reserve 5~10mm as the valid size |
| Thickness | ±0.5mm |
| Flatness | <3.0mm per 3m (Vertical and Horizontal) |
| Crack | Not Allowed |
| Chip, Void Corner | Not Allowed |
| Color Difference | Same Lot #: Same at 1m distance Different Lot #: Standard Sample Color Comparison |
| Blotch | Less than 4 defects within valid area |
| Pin Hole | Not obvious holes from 1m distance |
| Contaminant | Less than 4 defects (≤4mm) within valid area |
| Glossy | Minimum ≥ 40 |
| Scratch | No obvious scratch from 1m distance |
| Foreign Material | Not Allowed |
| Fissure | Not Allowed |
| Backside quality | Only less than 1mm size of hollows/ridges are acceptable |
| Polishing Mark | Not Allowed |